



Plastic Welding > Welding machines > BITUMAT

BITUMAT

The flameless welding machine welds modified bitumen(SBS, APP)at high speed.

- Consistent welding results
- Easy operation
- High welding speed
- Continuously adjustable heating and speed
- Pivotal steering bar enhances occupational safety
- Interchangeable driving roller simplifies cleaning
- Integrated bitumen scraper
- Electronic heating element protection



SPECIFICATIONS

BITUMAT 230V



Voltage	V~	230
Power consumption	W	6700
Frequency	Hz	50
Temperature	°C	20 - 650
Speed	m/min	0.8 - 12
Noise emission level LpA	dB	73
Welding seam width	mm	80 / 100
Size (L x W x H)	mm	690 x 490 x 330
Weight	kg	42 (with cord)
Approval mark		
Protection class I		

BITUMAT 400V

Voltage	V~	400
Power consumption	W	6700



Plastic Welding > Welding machines > BITUMAT

Frequency	Hz	50
Temperature	°C	20 - 650
Speed	m/min	0.8 - 12
Noise emission level LpA	dB	73
Welding seam width	mm	80 / 100
Size (L x W x H)	mm	690 x 490 x 330
Weight	kg	42 (with cord)
Approval mark		
Protection class I		

Plastic Welding > Welding machines > BITUMAT

ACCESSORIES



Bitumendüse für BITUMAT

127.691 - Bitumen nozzle 80 mm

127.690 - Bitumen nozzle 100 mm