



Plastic Welding > Tensiometer > EXAMO 300 F

## EXAMO 300 F

Ideal for measurements directly on the construction site.  
Optionally with data recording to a memory card. Clamp separation 300 mm.

- Designed for construction site conditions
- Handy, robust and light
- Digital display of elongation, peak force, tear force, test speed and position
- With optional data recording on a memory card
- Optionally for geotextiles



### SPECIFICATIONS

#### EXAMO 300 F 120 V

Type		300F
Voltage	V~	120
Power consumption	W	200
Frequency	Hz	50 / 60
Tensile load	N	4000
Jaw spacing	mm	5 – 300
Range	mm	300
Testing speed	mm/min	10 – 300
Sample thickness	mm	max. 7
Sample width	mm	max. 40 (60 optional)
Force sensor		yes
Memory card recording		optional
Size (L x W x H)	mm	750 x 270 x 190 (Storage case)
Weight	kg	14.0
Marking of conformity		CE



---

Plastic Welding > Tensiometer > EXAMO 300 F

---



Approval mark 

Protection class I 

---

EXAMO 300 F 230 V

---

Type		300F
Voltage	V~	230
Power consumption	W	200
Frequency	Hz	50 / 60
Tensile load	N	4000
Jaw spacing	mm	5 – 300
Range	mm	300
Testing speed	mm/min	10 – 300
Sample thickness	mm	max. 7
Sample width	mm	max. 40 (60 optional)
Force sensor		yes
Memory card recording		optional
Size (L x W x H)	mm	750 x 270 x 190 (Storage case)
Weight	kg	14.0
Marking of conformity		
Approval mark		
Protection class I		