



Plastic Welding > Tensiometer > EXAMO 600 F

EXAMO 600 F

Ideal for measurements directly on the construction site.
Optionally with data recording to a memory card. Clamp separation 600 mm.

- Designed for construction site conditions
- Handy, robust and light
- Digital display of elongation, peak force, tear force, test speed and position
- With optional data recording on a memory card
- Optionally for geotextiles



SPECIFICATIONS

Examo 600 F 120 V

Type		600F
Voltage	V~	120
Power consumption	W	200
Frequency	Hz	50 / 60
Tensile load	N	4000
Jaw spacing	mm	5 – 600
Range	mm	600
Testing speed	mm/min	10 – 300
Sample thickness	mm	max. 7
Sample width	mm	max. 40 (60 optional)
Force sensor		yes
Memory card recording		optional
Size (L x W x H)	mm	1050 x 270 x 190 (Storage case)
Weight	kg	17.5
Marking of conformity		CE





Plastic Welding > Tensiometer > EXAMO 600 F

Approval mark 

Protection class I 

Examo 600 F 230 V

Type		600F
Voltage	V~	230
Power consumption	W	200
Frequency	Hz	50 / 60
Tensile load	N	4000
Jaw spacing	mm	5 – 600
Range	mm	600
Testing speed	mm/min	10 – 300
Sample thickness	mm	max. 7
Sample width	mm	max. 40 (60 optional)
Force sensor		yes
Memory card recording		optional
Size (L x W x H)	mm	1050 x 270 x 190 (Storage case)
Weight	kg	17.5
Marking of conformity		
Approval mark		
Protection class I		