

Plastic Welding > Welding machines > TRIAC DRIVE PID

TRIAC DRIVE PID

Simple-to-use, semi-automatic overlap welding machine for universal deployment in all orientations.

- Overlap welding of PVC-P, ECB, EPDM, CSPE and TPO roofing membranes
- Faster and more efficient than hand welding
- Small and compact
- Steplessly adjustable speed for high welding seam quality
- Can be used in the most confined spaces
- Different welding seam widths



SPECIFICATIONS

TRIAC DRIVE 120 V

Voltage	V~	120
Power consumption	W	1700
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Speed	m/min	0.5 – 3
Noise emission level LpA	dB	65
Welding seam width	mm	30
Size (L x W x H)	mm	300 x 230 x 380
Weight	kg	4.15 (with 3 m cord)
Marking of conformity		CE
Approval mark		ISI
Certification scheme		CCA
Protection class I		⏚

TRIAC DRIVE 230 V

Voltage	V~	230
---------	----	-----






DHARMESH ENTERPRISES PVT. LTD.

Distributors & stocking house of hot air guns

B28/B, GR. FLR., GHATKOPAR INDL. ESTATE, L.B.S. MARG, GHATKOPAR(WEST), MUMBAI, MAHARASHTRA 400086

Website : www.hotairguns.com , www.heattool.com. Email : heatgun@vsnl.com

Plastic Welding > Welding machines > TRIAC DRIVE PID

Power consumption	W	1700
Frequency	Hz	50 / 60
Temperature	°C	20 – 600
Speed	m/min	0.5 – 3
Noise emission level LpA	dB	65
Welding seam width	mm	40
Size (L x W x H)	mm	300 x 230 x 380
Weight	kg	4.15 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class I		



Plastic Welding > Welding machines > TRIAC DRIVE PID

ACCESSORIES



Pressure roller for TRIAC DRIVE

- 115.274 - Pressure roller 12 mm
- 115.176 - Pressure roller 30 mm
- 115.186 - Pressure roller 38 mm



Guide handle for TRIAC DRIVE

- 115.284 - Guide handle



Single supporting carrier for TRIAC DRIVE

- 115.276 - Single supporting carrier



Double supporting carrier for TRIAC DRIVE

- 115.275 - Double supporting carrier



Overlap welding nozzle with/without grip, inside push-fit on TRIAC DRIVE

- 115.283 - Overlap welding nozzle 12 mm, with grip, inside, push-fit
- 115.279 - Overlap welding nozzle 30 mm, with grip, inside, push-fit
- 115.281 - Overlap welding nozzle 38 mm, with grip, inside, push-fit
- 115.699 - Overlap welding nozzle 12 mm, without grip, inside, push-fit
- 115.701 - Overlap welding nozzle 30 mm, without grip, inside, push-fit
- 115.703 - Overlap welding nozzle 38 mm, without grip, inside, push-fit



Overlap welding nozzle with/without grip, outside push-fit on TRIAC DRIVE

- 115.282 - Overlap welding nozzle 12 mm, with grip, outside, push-fit
- 115.278 - Overlap welding nozzle 30 mm, with grip, outside, push-fit
- 115.280 - Overlap welding nozzle 38 mm, with grip, outside, push-fit
- 115.698 - Overlap welding nozzle 12 mm, without grip, outside, push-fit
- 115.700 - Overlap welding nozzle 30 mm, without grip, outside, push-fit
- 115.702 - Overlap welding nozzle 38 mm, without grip, outside, push-fit