



Plastic Welding > Welding machines > UNIFLOOR E

## UNIFLOOR E

For welding floor coverings made of PVC-P, PE, linoleum and modified thermoplastics. With potentiometer and digital display for all the important welding parameters.

- Reproducible results thanks to digital display of set and actual values
- Electronically controlled heating
- Steplessly controlled air flow
- All floor coverings welded without reconfiguration
- Automatic start
- Integrated wall switch
- Unwind construction and trolley attachment as accessories available
- Compact, handy design



## SPECIFICATIONS

### UNIFLOOR E 120 V

Voltage	V~	120
Power consumption	W	1800
Frequency	Hz	50 / 60
Temperature	°C	20 - 620
Speed	m/min	1.0 - 7.5
Air flow (20°C)	l/min	300
Air flow range	%	50 - 100
Noise emission level LpA	dB	67
Size (L x W x H)	mm	420 x 270 x 215
Weight	kg	11.0 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA



Plastic Welding > Welding machines > UNIFLOOR E

Protection class I



UNIFLOOR E 230 V

Voltage	V~	230
Power consumption	W	2300
Frequency	Hz	50 / 60
Temperature	°C	20 - 620
Speed	m/min	1.0 - 7.5
Air flow (20°C)	l/min	300
Air flow range	%	50 - 100
Noise emission level LpA	dB	67
Size (L x W x H)	mm	420 x 270 x 215
Weight	kg	11.0 (with 3 m cord)
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class I		

Plastic Welding > Welding machines > UNIFLOOR E

ACCESSORIES



Welding rod de-reeler for UNIFLOOR E/S

115.054 - Welding rod de-reeler



Trolley attachment for UNIFLOOR E/S

115.057 - Trolley attachment