



Plastic Welding > Welding machines > UNIFLOOR S

UNIFLOOR S

For welding floor coverings made of PVC-P, PE, linoleum and modified thermoplastics. Without digital display. With potentiometer for welding speed and air temperature.

- Small, light and compact
- Integrated wall switch
- Adjustable airflow
- Electronically controlled heating and drive



SPECIFICATIONS

UNIFLOOR S 230 V

Voltage	V~	230
Power consumption	W	2300
Frequency	Hz	50/60
Noise emission level LpA	dB	67
Size (L x W x H)	mm	420 x 270 x 215
Weight	kg	14.0

UNIFLOOR S 120 V

Voltage	V~	120
Power consumption	W	1800
Frequency	Hz	50/60
Noise emission level LpA	dB	65
Size (L x W x H)	mm	420 x 270 x 215
Weight	kg	14.0

UNIFLOOR S 100 V

Voltage	V~	100
Power consumption	W	1500



Plastic Welding > Welding machines > UNIFLOOR S

Frequency	Hz	50/60
Noise emission level LpA	dB	65
Size (L x W x H)	mm	420 x 270 x 215
Weight	kg	14.0


Plastic Welding > Welding machines > UNIFLOOR S

ACCESSORIES



Trolley attachment for UNIFLOOR E/S

115.057 - Trolley attachment



Welding rod de-reeler for UNIFLOOR E/S

115.054 - Welding rod de-reeler